



NUTRUNNERS

HP 0,6 KW 0,44

Series 72/60



Performances and dimensions

Model	Free speed r/min	Speed at max power r/min	Torque at max power Nm	Starting torque Nm	Torque Nm	Quote "L" mm	Weight Kg.	Air consum l/sec.
M72/60LT5	85	42	88	100	130	200	3,2	8,5
P72/60LT5	85	42	88	100	130	190	3,2	8,5
M72/60N43	60	30	123	135	175	218	3,3	8,5
P72/60N43	60	30	123	135	175	208	3,3	8,5
M72/60NT3	45	22	169	185	240	218	3,3	8,5
P72/60NT3	45	22	169	185	240	208	3,3	8,5
M72/60P43	35	17	218	240	315	218	3,3	8,5
P72/60P43	35	17	218	240	315	208	3,3	8,5
M72/60PT3	25	12	309	320	420	218	3,3	8,5
P72/60PT3	25	12	309	320	420	208	3,3	8,5



ATTENTION

All data are based on a working pressure of 7 bar

Lubrication:

2-3 drops/1' continuous operation
4-6 drops/1' intermittent operation

Filtration:

Use 64 µ filtration or better

Axial load:

Not admitted

Operative temperature:

da-20° a +80°

